

## TECHNICAL DATA SHEET

**Item number:** 0600-391-021

**Product name:** CORRECTIVE PRIMER FOR ABS / PS PLASTICS

## CORRECTIVE PRIMER FOR ABS/PS PLASTICS

**Description:** A one-component corrective primer designed for heels and other ABS and PS accessories. The product covers up technical flaws of material – roughness and scratches. It dries fast and exhibits very good adhesion.

### RECOMMENDED USE

- direct spraying on to the plastic

### TECHNICAL PROPERTIES

• Density, (approx) kg/dm <sup>3</sup>	1,1
• Recommended film thickness per one coat, wet, µm.	25-35
• Recommended film thickness per one coat, dry, µm.	15-20
• Dry time (20 °C): 1st degree (tack-free), min	3-4
• Theoretical coverage at 25 µm film thickness dm <sup>3</sup> /m <sup>2</sup>	0,16
• Non-volatile ingredients (±2), % by volume	17
• Recommended number of coats	1

**GLOSS:** matte

**COLOR:** black

### PRODUCT APPLICATION

Contents should be stirred after opening the can.

### PRODUCT APPLICATION

#### Application methods:

One coat – conventional sprayer

- ▲ tip size 1,0-1,2 mm
- ▲ spraying pressure 3,0-3,5 atm

**Solvent:** item number 0602-50-004

Hardware cleaning: item number 0602-50-004

### APPLICATION

#### Surface

Plastic should be cleaned, degreased and free from other contaminants as they are the main cause of coating failure.

#### Painting and curing conditions

- surface temperature above 10°C
- good ventilation

**SHELF LIFE:** 9 months from the production date in original unsealed container.

**WARNING!** This product is designed for professional use in the given industry. Detailed information regarding product safety can be found in the MSDS.